

Product certificate

The company

TEUFELBESCHLAG GmbH

hereby certifies that the product

Sliding door System Variant HD Standard

has been tested on the basis of **EN 1527** by means of in-house control and long-time testing as a heavy suspended sliding door.

The product meets the following demands:

| | |
|---|--|
| Max. panel weight | 150 kg |
| Glass thickness in mm <ul style="list-style-type: none"> • tempered safety glass (ESG) • laminated safety glass (VSG) | 8 mm, 10 mm, 12 mm 10,76 mm, 11,52 mm, 12,76 mm |
| Number of cycles | > 100 000 |
| Functional capability | Class 6 |
| Initial friction | Class 3 |

Classification key according to EN 1527:

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| - | 6 | 3 | 0 | - | 0 | - | 1 | 3 |

When using Variant HD Standard a minimum panel width of 500 mm has to be ensured.

Moreover, in order to guarantee for an ideal functional capability a convenient width/height ratio of the glass panels is to be favoured.

Türkenfeld, 01.05.2018

TEUFELBESCHLAG GmbH
Am Brand 8
82299 Türkenfeld